

EA0404 Warden Intercom Point Firephone

INFORMATION SHEET

DESCRIPTION

The Tyco EA0404 Warden Intercom Point (WIP) is designed specifically for use in emergency warning systems. WIPs are used to communicate between floor wardens and the main emergency evacuation panel. When the handset is lifted, the Firephone automatically calls the emergency evacuation panel.

When the emergency evacuation panel calls the WIP, the call tone sounds through the speaker in the body of the phone. Lifting the handset automatically transfers from the phone body speaker to the handset speaker.

The EA0404 is CSIRO listed for use with Tyco QE90 and Simplex Fire Products QE90 EWIS panels and approved as compliant with AS2220.

The EA0404 comes packaged with screws to facilitate wall mounting and a comprehensive instruction sheet.

Refer to EWIS panel manuals for wiring details.

SPECIFICATIONS

Operating Voltage Operating Current (24Vdc) Frequency Response Line Impedance (selcetable) Call Tone Operating Temperature Relative Humidity (non-cond) Dimensions Weight **Part Number** 24Vdc 30mA 300 Hz to 3 kHz 600 Ohm/4k7 Ohm >80dB 1W/1m -10°C to +50°C 10 to 95% 210x80x72mm (HWD) 410g EA0404



www.tycosafetyproducts-anz.com

Tyco Safety Products, a division of Tyco Australia Pty Limited A.B.N. 80 008 399 004, reserve the right to alter specifications without notice, in line with Tyco's policy of continuing product improvement.

c:\0dove\productinformation\ea040403.indd EA0404 Issue 4

©Tyco Safety Products - Australasia

12 September 2005 Page 1 of 1

