

EA0009 'One Shot' 100mm 100V Line Surface Mount Speaker



EA0009 is designed to mount directly to the underside of concrete slabs or inaccessible ceilings. The housing is surface mounted with concealed internal fixings. Speaker cable entry can be either from the rear, or via surface mounted conduit (four 19mm conduit knockouts are provided). An excellent choice for use in plant rooms, warehouses, shopping centres, malls etc. The speaker is fitted with a 100V line transformer tapped at 0.33, 0.66, 1.25, 2.5 and 5W. Includes 4 way wire protected terminal strip and a 22 μ F bipolar capacitor for line monitoring applications in EWIS systems. It has a dual cone for extended frequency response. This speaker features 'One-Shot' design, simply snap-fits in seconds to the surface mounting ring, reducing installation time considerably.

Specifications

Power Rating	5W
Power Taps	0.33, 0.66, 1.25, 2.5, 5W
Sound Pressure Level	90dB 1W @ 1m
Frequency Response	100Hz - 15kHz
Operating Temperature	-25°C to +55°C
Relative Humidity	up to 95% (non-cond.)
Dimensions	210 dia. x 67H mm
Weight	900g
Part Number	EA0009



Step 1: Secure Housing to Mounting Surface



Step 2: Terminate Cable



Step 3: Fit Speaker to Housing