

## INFORMATION SHEET

### DESCRIPTION

The Tyco EA0313 Dual Strobe incorporates two visual notification appliances, to accommodate those applications where a two stage alarm system or two distinct visible signals are required.

The robust housing comes complete with four self tapping screws for fastening and four screw covers for aesthetics. The dual strobe has Alert and Evacuate labelling for amber and red lamps respectively.

### OPERATION


The strobes may be powered in tandem over a two wire circuit or four wire circuit and are mounted onto a moulded single gang backbox for installation ease and flexibility.

The Dual Strobes operate at 24 volts, with high powered 'U' type Xenon lamps providing a 2.6 Joule output ensuring high visibility.

When energised at 24VDC, the strobes will flash at approximately 100 flashes per minute. At higher voltages, the flash rate will be correspondingly higher.

The Lamp assemblies are raintight, made from high impact resistant ABS.

### Mounting Details



### Specifications

Operating Voltage	20 to 30Vdc
In Rush Current (24VDC)	290mA
Alarm Current (24VDC)	160mA
Luminescence	2.6J
Operating Temperature	-30°C to +60°C
Relative Humidity	10 to 95% (non-condensing)
Dimensions	250x150x80mm (HWD)
Mounting	Ø5.5x4 holes 226x126mm
Weight	450g
Construction	IP54
Part Number	EA0313